

UNITED STATES PATENT APPLICATION

TITLE: CRITICAL AND SUPERCRITICAL CLEANING OF HYDROCARBON-CONTAINING MATERIALS

INVENTOR: Ian Tunnicliffe and Raymond Mt. Joy

RELATED APPLICATION

This application claims provisional priority to United States Provisional Application Serial No. 60/265,825 filed 1 February 2000.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to an efficient and cost effective method for treating hydrocarbon-containing materials to remove solids, water, sulfur and/or other contaminants.

[0002] More particularly, the present invention relates to a method for cleaning hydrocarbon-containing materials including oil-containing materials such as well-fluids, drilling fluids, used oils, oil contaminated soils, or the like, under near critical, critical and/or supercritical conditions to produce a clean solid residue, an hydrocarbon residue and an aqueous residue, where the hydrocarbon residue is reusable, the solid residue is substantially free of hydrocarbons and aqueously extractable contaminants and the aqueous residue can be further cleaned to produce a purified water residue.

2. Description of the Related Art

[0003] Critical and supercritical extraction processes have been known for some time. Supercritical extraction has been used to clean oil and to desulfurize coal, but the technique has not been used to clean up drilling fluids so that the cutting are substantially free of hydrocarbon residue and/or aqueously soluble contaminants.

[0004] Thus, there is a need in the art for a method for cleaning drilling fluids and solid concentration derived therefrom generally via centrifugation to a purified solid material substantially free of hydrocarbon residues, drilling field chemicals and/or water soluble contaminants.

SUMMARY OF THE INVENTION

[0005] The present invention provides a solid residue substantially free of organic and/or non-organic water-soluble components, where the solid residue is derived from critical and/or supercritical extraction of a material including the solid, organic and/or non-organic water-soluble components with a cleaning composition comprising CO, CO₂, H₂O, lower alcohols, lower alkanes,

lower alkenes or mixtures or combinations thereof.

[0006] The present invention provides a water-insoluble liquid residue substantially free of solids and/or non-organic water-soluble components, where the liquid residue is derived from critical and/or supercritical extraction of a material including the solid, organic and/or non-organic water-soluble components with a cleaning composition comprising CO, CO₂, H₂O, lower alcohols, lower alkanes, lower alkenes or mixtures or combinations thereof.

[0007] The present invention provides a hydrocarbon residue substantially free of solids and/or water soluble components including organic and inorganic, water-soluble components or mixtures thereof, where the hydrocarbon liquid residue is derived from critical and/or supercritical extraction of a material including the solid, organic and/or non-organic water-soluble components with a cleaning composition comprising CO, CO₂, H₂O, lower alcohols, lower alkanes, lower alkenes or mixtures or combinations thereof.

[0008] The present invention provides a method for cleaning a solid material including contacting the mixture with a cleaning composition including CO, CO₂, H₂O, lower alcohols, lower alkanes, lower alkenes or mixtures or combinations thereof under conditions of temperature and pressure sufficient to maintain the cleaning composition at, near or above its critical point for a time sufficient to achieve a desired degree of cleaning of the solid material.

[0009] The present invention provides a method for cleaning a mixture including contacting the mixture with a cleaning composition including CO, CO₂, H₂O, lower alcohols, lower alkanes, lower alkenes or mixtures or combinations thereof under conditions of temperature and pressure sufficient to maintain the cleaning composition at, near or above its critical point for a time sufficient to achieve a desired degree of separation of the mixture.

[0010] The present invention provides a method for cleaning a mixture including contacting the mixture including a solid component, a water-insoluble liquid component and water with a cleaning composition including CO, CO₂, H₂O, lower alcohols, lower alkanes, lower alkenes or mixtures or combinations thereof under conditions of temperature and pressure sufficient to maintain the cleaning composition at, near or above its critical point for a time sufficient to achieve a desired degree of separation of the mixture into a solid residue, a water-insoluble liquid residue and an water-soluble liquid residue.

[0011] The present invention provides a method for cleaning a mixture including contacting the mixture including a solid component, a water-insoluble liquid component and water with a cleaning composition including CO, CO₂, H₂O, lower alcohols, lower alkanes, lower alkenes or mixtures or

[0016] The invention can be better understood with reference to the following detailed description together with the appended illustrative drawings in which like elements are numbered the same:

[0017] Figure 1 depicts a schematic diagram of a preferred embodiment of a batch type apparatus for carrying out the process of this invention;

[0018] Figure 2 depicts a phase diagram for carbon dioxide;

[0019] Figure 3 depicts a graph depicting the pressure verses enthalpy relationship for carbon dioxide;

[0020] Figure 4 depicts a schematic diagram of a preferred embodiment of a semi-batch apparatus for carrying out the process of this invention;

[0021] Figure 5 depicts a schematic diagram of one preferred embodiment of a continuous apparatus for carrying out the process of this invention;

[0022] Figure 6 depicts a schematic diagram of another preferred embodiment of a continuous apparatus for carrying out the process of this invention;

[0023] Figures 7A&B depict a schematic diagram of two preferred embodiment of a continuous apparatus for cleaning contaminated solid including drilling fluids, oil containing soils, or the like of this invention, where the extraction unit is shown in cross-section; and

[0024] Figures 8A&B depict a schematic diagram of two preferred embodiment of a continuous multi-staged apparatus of this invention for cleaning and/or desulfurizing used hydrocarbons including used motor oils or cleaning and/or desulfurizing hydrocarbon fuels including gasoline, fuel oil, diesel fuel, jet fuel or the like.

DETAILED DESCRIPTION OF THE INVENTION

[0025] The inventors have found that an efficient and cost effective process for cleaning solid materials and/or mixtures containing solid materials can be developed using a cleaning composition at, near or above is critical point. The processes of this invention can produce a solid residue substantially free of hydrocarbons, water soluble contaminants and/or other contaminants, a water-insoluble liquid residue substantially free of solids, water-soluble contaminants and/or other contaminants and a aqueous residue substantially free of solids and water-insoluble liquid contaminants.

[0026] The present invention broadly relates to a process for cleaning solids, dispersions, slurries, and/or liquids under near critical, critical or supercritical fluid extraction where the extracting fluid includes Xe, NH₃, lower aromatic including benzene and toluene, nitrous oxide, water, CO, CO₂,

10066294 013103

H₂O, lower alcohols including methanol, ethanol, propanol, and isopropanol, lower alkanes including methane, ethane, propane, butane, pentane and hexane, petroleum ether, lower alkenes including ethylene and propylene or mixtures or combinations thereof.

[0027] The process is ideally suited for cleaning drilling fluids, reactor sludge, oil-contaminated soils, oil contaminated water, used oil, hydrocarbon fuels such as diesel fuel, jet fuel and other similar hydrocarbon fuels, extracting oils from tar sands or the like, tanker bottoms, refinery bottoms, pit residues, refinery waste streams, refinery residue streams or the like. The pit residue include any material that comprises oil and solid materials such as soil, dirt or the like. The pit residue is generally associated with refining and/or separation and/or processing of crude oil streams. The present invention can also be used to extract hydrocarbon material out of paint wastes, polymer waste or any other chemical processing waste or waste stream that contains hydrocarbon materials, solid materials, water and/or other components that are amenable to near critical, critical and/or supercritical extraction.

[0028] The process results in purified hydrocarbons, purified solids, and/or purified water. However, near critical, critical and/or supercritical extraction is generally combined with other downstream water purification process to produce a purified water.

[0029] Drilling fluids are complex compositions that are the by-product of oil well drilling operations. These fluids can include solids from drilling operations, muds or other additives or compounds used in drilling operations, greases, anti-seize compounds, hydrocarbons from hydrocarbon bearing formations, water, heavy metals, fracturing compositions, proppants, or other ingredients and mixtures and combination thereof. Drilling fluids can be in the form of a mixture of liquids and solids, a dispersions, a suspension, an emulsion, or any other liquid like mixture of solids and liquids.

[0030] Drilling fluid solids are solids obtained from an initial separation of solids from liquid components of a drilling fluid mixture. The solids are generally obtained via centrifugation of the drilling fluids as is well-known in the art. The solids generally have the appearance of a tar like material, but can be any solid like material derived from a process which removes most liquid material from the drilling fluids.

[0031] The process is also ideally suited for cleaning hydrocarbon-containing fuels such as diesel fuel, jet fuel, home heating oil and other similar hydrocarbon fuels, or even gasoline. The process results in purified hydrocarbon-containing fuels having reduced sulfur contents and a sulfur containing residue. The fuel to be treated is contacted with a treating solvent or composition under

near critical, critical and/or supercritical conditions of temperature and pressure. The treatment temperature is usually from about 100°to about 400°C.

[0032] The process is also ideally suited for cleaning used motor oils to produce a reusable motor oil. Because the cleaning process removes material that are polar, many to all of the polar additives may be removed during the extraction system. Therefore, in one preferred reusable oil product of this invention, additives or additive packages are added into the cleaned oil. These additives can include any additive currently added to motor oils to improve their detergent properties or other properties.

[0033] Suitable extracting fluid include, without limitation, Xe, NH₃, lower aromatic such as benzene, toluene, or xylene, nitrous oxide, water, CO, CO₂, H₂O, lower alcohols such as methanol, ethanol, propanol, or isopropanol, lower alkanes such as methane, ethane, propane, butane, pentane hexane, or petroleum ether; lower alkenes such as ethylene or propylene; or mixtures or combinations thereof. Preferably, the extracting fluid includes carbon dioxide, water, lower alkanes, lower alcohols, or mixture or combinations thereof. Particularly, the extracting fluid comprises a major portion of CO₂ and a minor portion of a secondary fluid selected from the groups consisting of Xe, NH₃, lower aromatics, nitrous oxide, water, CO, H₂O, lower alcohols, lower alkanes, lower alkenes and mixtures or combinations thereof, where a major portion means greater than 50 mol% carbon dioxide, preferably, greater than 70 mol% carbon dioxide, particularly, greater than 90 mol% carbon dioxide, and especially, greater than 95 mol% carbon dioxide. More particularly, the extracting fluid is exclusively carbon dioxide.

[0034] Tabulated below are critical conditions for various supercritical fluids:

Fluid	Critical temperature T _c (°K)	Critical pressure P _c (MPa)	Critical Volume V _c (cm ³ /mol)
Carbon dioxide	304.14	7.375	94
Water	647.14	22.06	56
Ethane	305.32	4.872	145.5
Ethene	282.34	5.041	131
Propane	369.83	4.248	200
Xenon	289.73	5.84	118
Ammonia	405.5	11.35	75
Nitrous oxide	309.57	7.255	97

4006691.0 "T62900T"

Fluid	Critical temperature T _c (°K)	Critical pressure P _c (MPa)	Critical Volume V _c (cm ³ /mol)
Fluoroform	299.3	4.858	133
Methanol	190.56	4.599	98.60
Isopropanol	508.3	4.764	222
Toluene	591.75	4.108	316

[0035] For the purposes of this invention, the term substantially free means that the cleaned component includes less than or equal to about 5 wt% of any given contaminant, preferably, less than or equal to about 2.5 wt% of any given contaminant, particularly less than or equal to about 2 wt% of any given contaminant and especially less than or equal 1 wt% of any contaminant.

[0036] The material-to-be-treated is contacted with treating solvent under supercritical conditions of temperature and pressure. The term, "supercritical," "supercritical state," "supercritical conditions," or "supercritical conditions of temperature and pressure," refers to a temperature above the critical temperature (T_c) of the solvent being used, and a pressure above the critical pressure (P_c) of the solvent being used. The treatment temperature is usually from 470° to 630°K. All temperatures herein will be given in degrees Kelvin (°K) or degree Celsius (°C) unless otherwise stated. Treatment according to this invention is carried out at a reduced temperature (T_r) from 1.0 to about 1.4, preferably from about 1.05 to about 1.3, and at a reduced pressure (p_r) from 1.0 to about 2.0, preferably from about 1.05 to about 1.5. The term, "critical," "critical state," "critical conditions" or "critical conditions of temperature and pressure," refers to a solvent at its critical temperature, T_c, and its critical pressure, P_c. The term, "near critical," "near critical state," "near critical conditions" or "near critical conditions of temperature and pressure," refers to a solvent at most about 10°C below its critical temperature, T_c, and at most about 10 psi below its critical pressure, P_c, and preferably, at most about 5°C below its critical temperature, T_c, and at most about 5 psi below its critical pressure, P_c.

[0037] The solvent to material-to-be-treated ratio for treatment according to this invention can range from about 0.2 to about 3 kilograms of solvent per kilogram of material-to-be-treated (Kg/Kg) preferably from about 0.3 to about 1.0 Kg/Kg. Actually, the solvent to material-to-be-treated ratio is a dimensionless number, since both the amount of solvent and the amount of material-to-be-treated are expressed on a weight basis.

[0038] The present invention can make possible the use of a much lower solvent to material-to-be-treated ratio than those used in prior art processes at the lower end of the solvent to material-to-be-treated range. However, the process of the present invention can be operated at any ratio to achieve a desired result.

[0039] The solvent flow rate is generally from about 0.2 to 3 kilograms per hour of solvent per kilogram of material-to-be-treated per hour (*i.e.*, 0.2 to 3 kg/kg-hr). Preferably the solvent flow rate is about 0.5 kg/kg-hr. The time of treatment may range from about 0.5 to about two hours, and is preferably about one hour.

[0040] The material-to-be-treated may be treated in either a single stage or in plurality of stages (*i.e.*, in two or more stages). In single stage extractions or treatments, the composition of the treating solvent remains uniform over the entire course of treatment, and can be any solvent described above, but is preferably carbon dioxide alone or in combination with water, a lower alcohol or a lower hydrocarbon. In plural stage extractions or treatments, the composition of the treating solvent can be the same or different from stage to stage. For some using multi-staged treatment applications, the critical temperature of the treating solvent used in each stage increases progressively. Thus, the first stage solvent may be a carbon dioxide; next a mixture of carbon dioxide and water, or carbon dioxide and methanol; the solvent for the next stage may be, for example, a mixture of methanol and water with no carbon dioxide and so on. In extreme cases, the material-to-be-treated may be contacted consecutively with each of the treating fluids, *i.e.*, first with carbon dioxide, then with methanol, and finally with water, each in pure or substantially pure form. Whenever the composition of the solvent is varied over the course of treatment, the overall solvent composition (based on the total quantities of each treating fluid used over the entire course of treatment) is as stated above, *i.e.*, the mole fraction of carbon dioxide is from 0 to 0.5 (preferably 0.05 to 0.25), the mole fraction of methanol is from 0.20 to 0.70 (preferably 0.30 to 0.50), and the mole fraction of water is from 0.20 to 0.70 (preferably 0.25 to 0.65).

[0041] In many of the preferred processes of this invention, carbon dioxide alone is the preferred extraction fluid. Thus, in multistage application, only the amount of carbon dioxide being supplied to each stage may vary. Again, the carbon dioxide supplied in the first stage progresses with the material-to-be-treated to the next stage. Thus as additional carbon dioxide is supplied, the ratio to carbon dioxide to the material-to-be-treated changes. Additionally, each stage can be operated at a different temperature and/or pressure to achieve a desired final product.

[0042] For solid type materials, a fixed bed, a moving bed reactor or other similar reactors can be

used. Such reactor systems are described in more detail hereinafter. When the material-to-be-treated is a fluid (slurry, liquid, dispersion, suspension, mixture, or the like) at treatment temperature, a conventional stirred reactor or other type of batch, semi-batch or continuous reaction system can be used. For materials that include a large amount of solids such as drilling fluids, a preferred continuous system includes a tube within a tube within a tube type reactor described in more detail in disclosure associated with Figure 8. For materials, such as used motor oil, which generally, do not include a large amount of solids, a preferred system includes a series of extraction units described in more detail in the disclosure associated with Figure 9. This same type of multi-staged systems is ideally suited for reducing the sulfur content of hydrocarbon based fuels.

[0043] This invention will be further described and illustrated with reference to the drawings which represent preferred embodiments of systems for carrying out the processes of this invention, *i.e.*, processes designed to convert drilling fluids are solids therefrom into a cleaned solid residue, a non-aqueous residue and an aqueous residue.

System and System Operation

[0044] Referring now to Figure 1, a preferred embodiment of an extraction system generally 100 for use in the present invention is shown to include a source of a supercritical solvent 102, in this case carbon dioxide. The source 102 is connected to a sight glass 104 and a filter 106 via tubing 108. The tubing 108 is also connected to a rupture disk relief valve 110 for safety purposes. The filter 104 is connected to a pump 112 having a back pressure regulator 114 via tubing 108. The pump 112 is connected to a top entry 116 of an extraction cell 118 via tubing 108 including a pressure gauge 120, a supply control valve 122 and a second rupture disk relief valve 124. The cell 118 includes a bottom entry 126 and a sensor 128. The top entry 116 is also connected to a top outlet valve 130 via tubing 108; the bottom entry 124 is connected to a bottom outlet valve 132 and a bleed control valve 134, which is intern connected to a bleed valve 136. The top and bottom outlet control valves 130 and 132 are connected to a separation vessel 138 via a separator control 140 and a heat exchanger 142 including a second pressure gauge 144 and a bleed valve 146. The separator 138 includes a sensor 148, a carbon dioxide outlet 150 and a cleaned material outlet 152 having a control valve 154 which can be connected to a cleaned material container (not shown). The carbon dioxide outlet 150 connects to a used carbon dioxide venting line 156 includes a back pressure regulator 158, two filter 160, an flow regulator 162 and an exhaust line 164, which can be a recycle line by connecting the line to the pump 112. The entire system is amenable to computer control using standard computer control systems as are all of the other systems described herein.

generally is shown. The super critical fluid, CO₂, is fed into the extractor vessel whereupon the super critical fluid diffuses through the solids and removes the oil or hydrocarbons or other supercritical CO₂ soluble components, which contaminates the solid, into solution. The contaminants may be minerals, hydrocarbon (natural or synthetic). In the case of drilling fluid, the contaminants will also include additives to stabilize the drilling well fluids, including, without limitation, Polyalphaolefins, Acetals, Isomerised Olefins, Linear Alpha Olefins, Linear Alkylbenzenes, drilling muds or mixtures or combinations thereof or the like.

[0049] From the reactor vessel the solute loaded super critical fluid passes through a heated metering valve where it is depressurized and separation occurs, depositing the extracted oil and additives into the separation vessel. The super critical fluid (now in the gas phase) is exhausted to vent through a flow meter and totalizer. In a commercial full scale operation, the Carbon Dioxide gas or other fluid composition would be collected and fed back to the suction (low pressure) side of the pump, thereby creating a closed loop system. Samples of the extracted medium can be taken from the liquid phase to determine a desired degree of hydrocarbon removal. The chamber may require heating in certain circumstances.

[0050] The solid which was not taken into solution by the supercritical phase, remains in the reaction vessel for subsequent removal. After supercritical extration, the solid residue not only has reduced contaminants, preferably substantially no supercritically soluble contaminant, but is dry and a sterile.

[0051] Referring now to Figure 4, another preferred systems generally 400 for performing the extraction method of this invention is show where the extracting solvent is a mixture of carbon dioxide, pure water, and pure methanol. The pure water and pure methanol are contained in liquid form in feed reservoirs 402 and 404, respectively, having exit flow control valves 406 and 408, respectively. Liquid water and liquid methanol are introduced from reservoirs 402 and 404, respectively, into a liquid feed line 410. The water/methanol mixture is pumped through feed line 410 by means of a high pressure duplex reciprocating piston pump 412. This water/methanol mixture flows to a mixing tee 414.

[0052] Carbon dioxide is stored as a liquid under pressure in a pressure vessel 416, which may be a conventional gas cylinder. Carbon dioxide is withdrawn as a gas or vapor from the container 416 into a gas line 418. Carbon dioxide flow from the container 416 is controlled by a pressure regulator 420. The feed rate of carbon dioxide through the line 418 to the extractor 422 is controlled by a mass flow controller 424 and a control valve 426. Carbon dioxide is then passed through a pulse

suppressor 428 and a feed pre-heater 430 to insure smooth flow of the carbon dioxide stream to a gas compressor 432. Carbon dioxide is then compressed in the gas compressor 432 and the flow of compressed carbon dioxide is stabilized by passing it through a flow stabilizer 434. The carbon dioxide stream flows from the stabilizer 434 to the mixing tee 414.

[0053] The carbon dioxide stream is then mixed with the methanol/water mixture in the mixing tee 414. The combined mixture is then pre-heated in a feed pre-heater 436 to a temperature close to but slightly below the desired reaction temperature. The heated solvent mixture is then fed via a solvent feed line 438 to the extractor 422, which has a fixed or stationary bed 440 therein. The fixed bed 440 is designed to contain an amount of a composition to be subjected to supercritical extraction, where the composition is either drilling solids from a centrifuge or drilling fluids directly for a well site.

[0054] The extractor 422 is of a generally vertical tubular shape – a vertically disposed tubular reactor, which is surrounded by a heating jacket 442 having an electric heater 444 positioned therein. A foraminous plate 446 at a bottom 448 of the extractor or reactor 422 supports the bed 440. The extractor 422 is provided with a rupture disc 450 and a pressure gauge 452. The extractor 422 is also provided with a temperature sensor or indicator 454, which indicates the temperature in the bed 440, and a temperature controller 456, which controls the current to the electric heater 444 in response to a reaction temperature as sensed by temperature indicator 454.

[0055] During extraction, the extractor is held under conditions of temperature and pressure sufficient to maintain the solvent at, near, but below or above the solvents critical point – maintained under near critical, critical or supercritical conditions – as it passes downwardly through the bed 440. The effluent exits the reactor 422 at an outlet 458 and the effluent will include the solvent and some or all components soluble in the solvent (depending on the degree of intended cleaning or treatment) from the material-to-be-treated in the bed 440 such as organics, inorganics or the other compounds soluble in the extraction solvent under near critical, critical or supercritical conditions. The rate of removal of the exiting solvent is controlled by a control valve 460, which may be a needle valve. The normally liquid components of the effluent, *i.e.*, water, methanol, and liquids extracted by the solvent are condensed by passage through a tubular condenser 462. The condenser 462 is cooled by any suitable means such as a dry ice-acetone bath 464. The condensed liquids may be removed periodically (*e.g.*, at the end of a run) from the condenser 462 for analysis. Uncondensed gases, typically carbon dioxide and normally gaseous hydrocarbons, are vented from the condenser 462 through a vent line 466. These gases may be analyzed as desired and the carbon

dioxide recovered for recycling. Additionally, the volatile hydrocarbons can be collected for further processing. The calorific value of the vent gases in the line 464 may be recovered, *e.g.*, by combustion of the gas mixture, where the calorific value is sufficient to justify this. Of course, if the above reaction system is run using only one solvent component, then the other solvent component feed lines are simply turned off or by-passed.

[0056] According to a preferred embodiment of a process of this invention, centrifuged drilling solids and/or fluids are charged to the reactor 422 prior to the start of a run. Water, methanol and carbon dioxide are fed to the reactor 422 in desired proportions, which can run from pure carbon dioxide, pure methanol, pure water or any mixture or combination thereof. The respective feed rates are controlled by means of the valves 406 and 408 and the mass flow controller 424. The solvent feed mixture is pre-heated in pre-heater 436 to a temperature just below the critical temperature of the solvent composition. The solvent mixture is passed downwardly through the bed 440 in the reactor 422, where it is operated under conditions of temperature and pressure sufficient to maintain the solvent near its critical point, at its critical point or above its critical point – near critical condition, critical conditions or supercritical conditions – by means of external heat supplied by the electric heater 444. The effluent exiting the reactor 422 includes the solvent and all solvent soluble components with the solid being left in the bed 440 is continuously removed and is condensed as previously described. A run is allowed to proceed either for a predetermined length of time or for a length of time determined by some other parameter, such as instantaneous effluent analysis. Normally the solvent composition, *i.e.*, the relative proportions of water, methanol and carbon dioxide, will remain constant throughout a run. This mode of operation may be described as semi-batch, since the solids and/or fluids are charged to and the solids are discharged from the extractor 422 before and after a run, respectively, in accordance with batch operation principles, while the solvent mixture is fed continuously throughout a run. Of course, the reaction can be run with non-continuous solvent feed, which would be under purely batch operating principles.

[0057] Semi-batch operation as described in Figure 4 may be carried out in two or more stages, using solvents of different compositions in each stage. The solvent used in each stage may be Xe, NH₃, lower aromatic including benzene and toluene, nitrous oxide, water, CO, CO₂, H₂O, lower alcohols including methanol, ethanol, propanol, and isopropanol, lower alkanes including methane, ethane, propane, butane, pentane and hexane, petroleum ether, lower alkenes including ethylene and propylene or mixtures or combinations thereof. Using valves and flow controllers, an operator can pass a solvent of any desired composition into an appropriate extractor. When more than one stage

is used, the first stage (the earliest portion of the run) typically uses the most volatile solvent (*i.e.*, the solvent having the lowest critical temperature), and the solvent or solvent mixtures used in subsequent operating stages typically have progressively higher critical temperatures. However, each stage can use the same solvent composition.

[0058] The present invention can also be operated under continuous operating conditions using reactors systems such as those illustrates in Figures 5 and 6. Referring now to Figure 5, a preferred continuous system generally 500 for performing the extraction method of this invention is shown to include a stirred high-pressure vessel 502, which serves to mix the material-to-be-treated such as drilling fluids or a solids with the solvent. The material-to-be-treated and the supercritical extraction solvent are fed to the vessel 502 via a feed line 504 and a solvent feed line 506, respectively. The solvent entering through the line 506 is a solvent selected from the group consisting of Xe, NH₃, lower aromatic including benzene and toluene, nitrous oxide, water, CO, CO₂, H₂O, lower alcohols including methanol, ethanol, propanol, and isopropanol, lower alkanes including methane, ethane, propane, butane, pentane and hexane, petroleum ether, lower alkenes including ethylene and propylene or mixtures or combinations thereof. The resulting slurry, dispersion or mixture is then pumped by a high-pressure slurry pump 508 through a feed preheater 510, which serves to heat up the mixture to a temperature just below the extraction temperature. The preheated feed is then admitted through a ball valve 512 or other similar device into a supercritical extractor 514 which is of the stirred reactor design, a mixing extruder, or other similar high shear mixing reactors. The mixture containing the extracted non-solid components is passed through a discharge valve 516 into a product cooler 518. The cooled product is next sent to a separating vessel 520 in which the gaseous product of extraction are separated from the cleaned solids and the liquid products. The gaseous product are either vented from the system 500 through valve 522 or separated to recover carbon dioxide or to a system to recover hydrocarbons or to recover fuel equivalents thereof. The solid and liquid products are removed through a valved discharge line 524.

[0059] Referring now to Figure 6, another configuration for a continuous supercritical extraction system generally 600 for performing the extraction method of this invention is shown to include a storage hopper 602 containing a solid material-to-be-treated such as drilling solids, where a level of solids in the hopper 602 is controlled via a solid level indicator-controller 604. The solids are metered from the storage hopper 602 through a rotary air lock feeder 606 or via a screw type extruder or other similar apparatus into an extractor 608. A solvent mixture is fed into the extractor 608 through a solvent feed line 610. This solvent is selected from the group consisting of Xe, NH₃,

lower aromatic including benzene and toluene, nitrous oxide, water, CO, CO₂, H₂O, lower alcohols including methanol, ethanol, propanol, and isopropanol, lower alkanes including methane, ethane, propane, butane, pentane and hexane, petroleum ether, lower alkenes including ethylene and propylene or mixtures or combinations thereof, which may be formed, pressurized and preheated to just below the critical temperature as described with reference to Figure 5. The solvent can be analyzed for compositional makeup using a gas chromatograph 612. The system shown in Figure 6 differs from that shown in Figure 5 in that the system of Figure 5 can be operated only co-currently, while the system of Figure 6 can be operated either under counter-current or co-current flow conditions. A mixture of extracted and cleaned solids discharged from the extractor 608 is cooled in a product cooler 614 before being let down through a valve 616 into a product separating vessel 618. In this vessel, the gaseous products of extraction are separated from the cleaned solids and the liquid products. The gaseous product is then vented from the system through a valve 620. The cleaned solids and liquid products are discharged through a valve 622 and separated as described above.

[0060] Referring now to Figures 7A&B, a preferred configuration for a continuous supercritical extraction system, generally 700, for performing the extraction method of this invention for solid and/or slurry materials is shown to include an input container 702 containing a solid material-to-be-extracted 703 such as drilling fluids.

[0061] The solids are metered from the container 702 through a control/metering system 704 into an extractor 706 via lines 707, where the control/metering system 704 can be a pump, a rotary air lock feeder, a screw type extruder, a valve, or other control/metering apparatus. If the container 702 is pressurized, the controller 704 can be a remote controlled valve, but generally, the controller 704 is a pump.

[0062] The extractor 706 comprises a tube within a tube within a tube type extractor. The extractor 706 includes an outer column or tube 708a, a semi-permeable membrane 710, a lower section 712a and an upper section 712b. The upper section 712b includes a closed ended, inverted middle tube 708b and an inner tube 708c. The extractor 706 also includes a material-to-be-extracted inlet 714 connected to one of the lines 707 from the controller 704A. The inlet 714 passes through the membrane 710 delivering the material-to-be-extracted 703 into an interior 716 of the inner tube 708c from the container 702. The dashed lines with arrows indicate the direction of material flow in the extractor 706. The inner tube 708c extends upward to form a first gap 718a between a top 720 of the inner tube 708c and an inner surface 722 of the closed end 724 of the middle tube 708b. The

middle tube **708b** extends downward to form a second gap **718b** between a top **711** of the membrane **710** and a bottom **726** of the middle tube **708b**. While a third gap **718c** is formed between an outer surface **728** of the closed end **724** of the middle tube **708b** and an inner surface **730** of a top **732** of the column **708a**. The inner surface **730** is shown here to include a tapered section **731** to improve material flow out of the extractor **706**. The gaps **718a**, **718b** and **718c** may have the same dimension or may have different dimensions and are designed to provide shear mixing of the material-to-be-extracted and the extracting fluid as the combined flow progressed through the extractor **706** along the path indicated by the dashed and arrowed lines.

[0063] The extractor **706** also includes extraction fluid inlets **734a**, **734b** and **734c** adapted to supply an extraction fluid **736** from an extraction fluid supply system **738** to the extractor **706** via lines **735a-c**. The inlet **734c** supplies a first amount of extraction fluid **736** into the inner tube **708c** at a position **740** near a top **715** of the inlet **714** via line **735c**. The inlet **734b** supplies a second amount of extraction fluid **736** via line **735b** into the middle tube **708b** at a position **742**. The position **742** can be at any desired location along the middle tube **708b**, but is preferably located near the gap **718b**. The inlet **734a** supplies a third amount of extraction fluid **736** via line **735a** into the outer tube **708a** at a position **744**. Although the position **744** can be located anywhere along the column **708a**, it is preferably located near the gap **718b**.

[0064] The supply system **738** includes an extraction fluid storage tank **746**, a compressor **748**, and a mass controller **750**. The compressor **748** compresses the extraction fluid **736** to a desired pressure, which is preferably a pressure that is sufficient to maintain the extraction fluid in the extractor to be at or above the supercritical point for the particular extraction fluid being used. Looking at Figure 7A, the system **738** also includes separate valves **752a-c** for controlling the first, second, and third amount of extracting fluid flowing into the extractor **706** through lines **735a-c** and a fourth valve **752d** controlling the amount of extraction fluid **736** supplied, via line **735d**, to a venturi valve described below. Looking at Figure 7B, the system **738** includes only a single valve **752** for controlling the amount of extracting fluid flowing into the extractor **706** through lines **735a-c** and into the venturi valve via line **735d**. In both Figures 7A&B, the supply system **738** also includes a recycle line **754**.

[0065] As the material-to-be-extracted **703** is being feed and mixed with the extraction fluid **736**, any water and materials dissolved in the water migrate across the membrane **710** into the lower section **712a** and exit the extractor **706** via a line **713** to an aqueous phase storage tank **756** via a control valve **758a** and a heat exchanger **758b**, where the control valve **758a** reduces the pressure

to ambient pressure.

[0066] After the material-to-be-extracted 703 has been mixed with the three portions of extraction fluid 736 in the extractor 706, the combined mixture exits the extractor 706 via exit line 760 which interconnects the extractor 706 with a first separator 762. The separator 762 allows the solids to sink to a bottom section 764a of the separator 762, while the fluids occupy a top section 764b of the separator 762. The separator 762 also includes a venturi valve 766 connected to an extraction fluid input 768 connected to the supply line 735d from the extraction supply system 738. As the extraction fluid 736 travels through the venturi valve 766, the solids 770 are pulled into the venturi valve 766 and exit the separator 762 to a solids recovery system 772 via a solids outlet 771. The solids recovery system includes a solids storage vessel 772a connected to the separator 762 via lines 772b having a pressure reducing control valve 772c and a heat exchanger 772d. The separator 762 can also include a by-pass outlet 769 for the extraction fluid supplied to the venturi valve 766 via inlet 768.

[0067] The liquids, oils and extraction fluid, from the first separator 762 are forwarded to a second separator 774 through two pressure-reducing control valves 776a&b and two heat exchangers 778a&b via lines 779. The second separator 774 includes hydrocarbon liquid exit line 780 connected to a hydrocarbon storage vessel 781 via control valve 782. The second separator 774 also includes probes 784, that determine the liquid level 785 in the separator 774, and an extraction fluid exit 786 connected to the extraction fluid recycle line 754. Additionally, the extraction fluid by-pass outlet 769 from the venturi valve 766 is directed via line 788 to a by-pass valve 789 and a regulator valve 790 and combined with the liquids from the first separator 762 at the heat exchanger 778a.

[0068] The preferred extraction fluid for use in the extraction system 700 is pure carbon dioxide, but the extraction fluid can be selected from the group consisting of Xe, NH₃, lower aromatic including benzene and toluene, nitrous oxide, water, CO, CO₂, H₂O, lower alcohols including methanol, ethanol, propanol, and isopropanol, lower alkanes including methane, ethane, propane, butane, pentane and hexane, petroleum ether, lower alkenes including ethylene and propylene or mixtures or combinations thereof, which may be formed, pressurized and preheated to just below the critical temperature as described with reference to Figure 5.

[0069] The apparatus of the present invention can be located remote from the drilling site or can be integrated into the drill complex. Thus, an off-shore drilling platform could have an extraction unit built onto the pumping system for the drilling fluids so that the solids and aqueous components could be separated on the hydrocarbon components which would include mud ingredients could be

fed back into the downhole fluid stream.

[0070] Referring now to Figure 8, a preferred configuration of a continuous supercritical extraction system generally **800** of this invention for cleaning and/or desulfurizing liquids with only minor amount of solids therein, such as used motor oils or fuels, is shown to include a material-to-be-treated supply system **802**. The material-to-be-treated supply system **802** includes a material-to-be-treated reservoir **804** containing the material-to-be-treated **806**, a pump **808** or any other apparatus for transferring a liquid material and a feed line **810**.

[0071] The system **800** also includes an extracting fluid supply system **812**. The extraction fluid supply system **812** includes an extracting fluid reservoir **814** containing an extraction fluid **815**, a compressor **816**, an extraction fluid feed line **818** and a recycle line **820**.

[0072] The system **800** is a multi-staged extraction/cleaning system shown in Figure 8 to have four extractors **822a-d** in series and a separator **824**. Each extractor **822** includes a membrane **826** separating each extractor **822** into an upper section **828** and a lower section **830**. The membranes **826** allow water and polar compounds to migrated from the upper section **828** of each extractor into the lower section of each extractor. The first extractor **822a** is connected to the material-to-be-treated feed line **810**, while the other three extractors **822b-d** include a forwarding line **832**, which feeds the extractors **822b-d** with the contents of the upper section **828** of the preceding extractor **822a-c**, i.e., the contents of the upper section **828** of the extractor **822a** is the feed for the extractor **822b** via forwarding line **832** and so on. Finally, the contents of the upper section **828** of the extractor **822d** are forwarded to the separator **824** via a separator feed line **834**. Each extractor **822** also includes an extractor feed line **836** connected to the feed line **818**. Looking at Figure 8B, each feed line **836** includes a separate flow controlling valve **838**, where the valves **838** allow the amount of extraction fluid **815** entering each extractor **822a-d** to be separately controlled so that the amount of extraction fluid **815** being supplied to each extractor **822a-d** can be different. Each extractor **822a-d** also includes an aqueous phase outlet **840** connected to a waste aqueous storage system **842** via waste lines **844**. The storage system **842** includes a pressure reduction valve **846** and a heat exchanger **848** to reduce the pressure to ambient pressure and allow the temperature to warm to room temperature and a waste water storage container **850**. The waste water can be forwarded to a water treatment facility for further processing.

[0073] The separator **824** includes a finished product outlet **852** and an extraction fluid outlet **854**. The finished product outlet **852** is connected to a finished product storage system **856** via finished product line **858**. The finished product storage system **856** includes a pressure reduction valve **860**

and a heat exchanger 862 to reduce the pressure to ambient pressure and allow the temperature to warm to room temperature and a finished product storage container 864. The extraction fluid outlet 854 is connected to the recycle line 820 passing through a pressure reduction valve 866 and a heat exchanger 868 to reduce the pressure to ambient pressure and allow the temperature to warm to room temperature prior to mixing with the fresh extraction fluid going into the compressor 816.

[0074] Although any extraction fluid described in this invention can be used in the systems of Figures 7A&B and 8A&B, the system preferably uses pure carbon dioxide.

[0075] Additionally, if carbon dioxide is used in the extraction solvent composition, then any of the previously described installation can be equipped with a low temperature separator for separating carbon dioxide out of the atmosphere. Additionally, the apparatus can have recycling equipped to recover the extraction solvent for recycling.

EXPERIMENTAL RESULTS

[0076] The supercritical extraction solvent used in the following examples was standard commercial grade Carbon Dioxide, from a stock cylinder. The type of cell used in the following examples was an 8 mL stainless steel view cell. The pump type used in the following examples was a Milton Roy 100ml/hour max, positive displacement pump. The samples used in the following examples was a sample as received from Baker Hughes and was centrifuged cuttings from well fluids. In all of the examples the follow, the oil removal % was estimated or derived by sight only.

Example 1

[0077] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 3,500 psi.

[0078] The supercritical extraction cell and pipework were cleaned with acetone. 1 g of the sample was placed in the cell and the cell was reassembled. The cell was then placed into supercritical pipe circuit. The cell and pipework were flushed twice with stock Carbon Dioxide. The pressure was then increased to about 3,500 psi at ambient temperature. No color change in liquid phase was noted. The pressure was held at about 3,500 psi pressure for about 1 hour and 20 minutes. The total oil removed from the sample was about 99%. The solid material had a slight hydrocarbon sent, but dry to the touch.

Example 2

[0079] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 1,000 psi and at 25°C.

[0080] The cell was cleaned and prepared as described in Example 1. After preparation, the

pressure was increased to about 1000 psi at a temperature of about 25°C. The pressure and temperature were maintained for about 1 hour. Under these conditions only partial oil removal was achieved with the recovery being about 60%.

Example 3

[0081] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 2,000 psi and at 27.8°C.

[0082] The cell was cleaned and prepared as described in Example 1. After preparation, the pressure was increased to about 2000 psi at a temperature of about 27.8°C. The pressure and temperature were maintained for about 20 minutes. Under these conditions only partial oil removal was achieved with the recovery being about 85%.

Example 4

[0083] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 2,500 psi and at 22.5°C.

[0084] The cell was cleaned and prepared as described in Example 1. After preparation, the pressure was increased to about 2500 psi at a temperature of about 22.5°C. The pressure and temperature were maintained for about 10 minutes. Under these conditions only partial oil removal was achieved with the recovery being about 95%.

Example 5

[0085] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 3,500 psi and at 43°C.

[0086] The cell was cleaned and prepared as described in Example 1. After preparation, the pressure was increased to about 3500 psi at a temperature of about 43°C. The pressure and temperature were maintained for about 5 minutes. Under these conditions only partial oil removal was achieved with the recovery being about 95%.

Example 6

[0087] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 2,500 psi and at 43°C.

[0088] The cell was cleaned and prepared as described in Example 1. After preparation, the pressure was increased to about 2500 psi at a temperature of about 43°C. The pressure and temperature were maintained for about 5 minutes. Under these conditions only partial oil removal was achieved with the recovery being about 95%.

Example 7

[0089] This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 2,500 psi and at 23°C.

[0090] The cell was cleaned and prepared as described in Example 1. After preparation, the pressure was increased to about 2500 psi at a temperature of about 23°C. The pressure and temperature were maintained for about 5 minutes. Under these conditions only partial oil removal was achieved with the recovery being about 97%.

Example 8

This example illustrates the cleanup of a sample of oil laden solids obtained after well fluids are subjected to centrifugation under supercritical conditions using CO₂ at 2,500 psi and at 23°C.

[0091] The cell was cleaned and prepared as described in Example 1. After preparation, the pressure was increased to about 2500 psi at a temperature of about 23°C. The pressure and temperature were maintained for about 2 minutes. Under these conditions only partial oil removal was achieved with the recovery being about 80%.

Example 9

[0092] This example illustrates an analysis of a used oil after supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0093] The following table lists the properties of the treated oil:

Test	Common Name	Test Units	Results
ASTM D 482-95	Viscosity Index	wt%	0.365
ASTM D 93	Flash Point by PMCC	°F	230+
ASTM D 1296-99	API Gravity @60°F	°API	28.8
ASTM D 4077	Water Content	vol%	6.32
ASTM D 445	Kinematic Viscosity @100°F	cSt	24.470
ASTM D 4294-98	Total Sulfur	wt%	0.327

Example 10

[0094] This example illustrates the comparison of used oil before and after supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0095] The following table lists the properties of the oil before treatment:

Test	Common Name	Test Units	Results
ASTM D 482-95	Ash Content	wt%	0.365
ASTM D 93	Flash Point by PMCC	°F	230+
ASTM D 1296-99	API Gravity @60°F	°API	28.8
ASTM D 4077	Water Content	vol%	6.32
ASTM D 445	Kinematic Viscosity @100°F	cSt	24.470
ASTM D 4294-98	Total Sulfur	wt%	0.327

[0096] The following table lists the properties of the oil after treatment:

Test	Common Name	Test Units	Results
ASTM D 482-95	Ash Content	wt%	0.005
ASTM D 93	Flash Point by PMCC	°F	190
ASTM D 1298	API Gravity @60°F	°API	33.9
ASTM D 4052	API Gravity @60°F	°API	33.9
ASTM D 4077	Water Content	vol%	0.08
ASTM D 445	Kinematic Viscosity @100°C	cSt	2.904
ASTM D 445	Kinematic Viscosity @100°F	cSt	11.62
ASTM D 445	Kinematic Viscosity @40°F		10.71
ASTM D 2887-97a - Ext'd	Distillation, 99% Recovery	°F	924
ASTM D 1500-98	Color	ASTM	L 2.0
ASTM D 2270-93	Viscosity Index		124
ASTM D 4530-93	Carbon Residue (micro method)		<0.1
ASTM D 4294-98	Total Sulfur	wt%	0.244
ASTM 6762	Nitrogen	mg/Kg	46.0
AAS by Acid Digestion	Iron	ppm-wt	0.4
AAS by Acid Digestion	Nickel	ppm-wt	<0.1
AAS by Acid Digestion	Copper	ppm-wt	0.2

Example 11

[0097] This example illustrates the comparison of used oil before and after supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0098] The following table lists the properties of the oil after treatment:

Test	Value	Test	Value
Viscosity Index, D-2270	85	Viscosity CST @40°F, D-445	31.38
Appearance	Clear & Bright yellow liquid	Pour Point, °F, D-97	<-10
Odor	Petroleum	Sulfur wt%, D-4294	0.2802
Viscosity SUS @210°F, D	43.0	Ash wt%, D-482	<0.001
Viscosity SUS @100°F, D-445	154.1	Color, D-1500	1.5
Gravity API @	31.8	Actual flash point, COC D-92	400°F
Flash point, S.W. 101, °F	230+	Metals	0.10

Example 12

[0099] This example illustrates the comparison of used oil before and after supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0100] The following table lists the properties of the oil before and after treatment:

Spec	Before	After	Diff	%Diff	+/-
Ash	0.365	0.005	0.360	98.6	Decrease
Water	6.32	0.03	6.29	99.5	Decrease
Viscosity	24.47	2.904	21.566	88.1	Decrease
Flash	190	230	40	21	Increase
API Gravity	28.8	33.9	5.1	17.7	Increase
Sulfur	0.337	0.244	0.093	27.7	Decrease

Example 13

[0101] This example illustrates the comparison of used oil before and after supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0102] The following table lists the properties of the oil before and after treatment:

Spec	Before	After	Diff	%Diff	+/-
Ash	0.4	0.02	0.38	95	Decrease
Water	6.4	0.4	6.0	93.75	Decrease
Flash	200+	200+	----	---	---
Sulfur	0.3	0.3	---	---	---

Example 14

[0103] This example illustrates the comparison of used oil before and after supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0104] The following table lists the properties of the oil before and after treatment:

Parameter	Test Method	Detection Limit	Before	After
Gravity API@60°F	D-287	---	28.2	29.7
Flash Point, °F	S.W. 1010	-10	BFO	380
Viscosity CST @40°C	D-445	1	24.37	35.63
Pour Point, °F	D-97	-10	<-10	<-10
Sulfur, wt%	D-4294	0.0001	0.3116	0.3019
Ash, wt%	D-482	0.001	0.315	0.004
Total Halogen, PPM	D-808	1.0	617.2	10.6
PCB's, PPM	S.W. 8082	0.05	BDL	BDL
Water by distillation, Vol%	D-95	0.05	6.4	<0.05
Sediment by Extraction, wt%	D-473	0.01	0.05	<0.01
Heat of Combustion, BTU/lb	D-240	10	17,761	19,302
Heat of Combustion, BTU/gal	D-240	60	131,040	141,078
Carbon Residue Ramsbottom, wt%	D-524	0.01	---	0.06

Heavy Metals PPM	Method	Detection Limit	Before	After
Arsenic	EPA-6010	0.0012	BDL	BDL
Cadmium	EPA-6010	0.0015	0.113	0.014
Chromium	EPA-6010	0.0040	0.525	0.007
Lead	EPA-6010	0.0140	9.693	0.338
Nickel	EPA-6010	0.0055	4.021	BDL
Sodium	EPA-6010	0.0010	66.277	1.823
Vanadium	EPA-6010	0.0020	0.030	0.015
Iron	EPA-6010	0.0015	31.981	0.351

BDL- beyond detection limit; BFO- Blows flame out @200°F

Recovery, D-86	Distillation, °F	Recovery, D-86	Distillation, °F
IBP	542	70% Recovery	728
5% Recovery	602	80% Recovery	740
10% Recovery	670	90% Recovery	756
20% Recovery	690	95% Recovery	788
30% Recovery	700	End Point	796
40% Recovery	708	Recovery	98.0%
50% Recovery	714	Residue	1.5%
60% Recovery	718	Loss	0.5%

Example 15

[0105] This example illustrates the analytical data for the oil extracted from a drilling fluid under supercritical cleanup using the apparatus of this invention and CO₂ as the extracting fluid.

[0106] The following table lists the properties of the drilling fluid recovered oil:

Parameter	Test Method	Results
Gravity API@60°F	D-287	38.0
Flash Point, PMCC °F	D-93	148
Viscosity CST @100°F	D-445	2.73
Pour Point, °F	D-97	-5
Cloud Point, °F	D-2500	10
Sulfur, wt%	D-4294	0.0615
Ash, wt%	D-482	<0.001
Color	D-15	0.5
PCB's, PPM	S.W. 8082	BDL
Water by distillation, Vol%	D-95	<0.05
Sediment by Extraction, wt%	D-473	<0.01
Carbon Residue Ramsbottom, wt%	D-524	0.06
Carbon Residue Ramsbottom, wt% on 10% residue	D-524	0.20
Cetane Index	D-976	54.0
Bacteria Count, Counts/mL	---	0
Heavy Metals PPM	Method	Before
Arsenic	EPA-6010	BDL
Cadmium	EPA-6010	BDL
Chromium	EPA-6010	0.006
Lead	EPA-6010	0.254
Nickel	EPA-6010	BDL
Sodium	EPA-6010	0.572
Vanadium	EPA-6010	BDL
Iron	EPA-6010	0.039

BDL- beyond detection limit; BFO- Blows flame out @200°F; same detection limits as in Example

Recovery, D-86	Distillation, °F	Recovery, D-86	Distillation, °F
IBP	354	70% Recovery	578
5% Recovery	396	80% Recovery	600
10% Recovery	408	90% Recovery	636
20% Recovery	438	95% Recovery	674
30% Recovery	460	End Point	698
40% Recovery	482		
50% Recovery	528		
60% Recovery	554		

Accelerated Stability, F 21-61	Value
Initial Color	0.5
Final Color	1.0
Pad Rating (Blotter)	1

[0107] All references cited herein are incorporated by reference. While this invention has been described fully and completely, it should be understood that, within the scope of the appended claims, the invention may be practiced otherwise than as specifically described. Although the invention has been disclosed with reference to its preferred embodiments, from reading this description those of skill in the art may appreciate changes and modification that may be made which do not depart from the scope and spirit of the invention as described above and claimed hereafter.